

MATERIAL SAFETY DATA SHEET

SECTION 1 - MATERIAL IDENTIFICATION

| | | | |
|----------------------|-------------------------|-----------------------|-----------------|
| Product Name: | Stazon Blockout Thinner | Manufacturer: | FMS Corporation |
| | | Date Prepared: | May 1, 2011 |

SECTION 2 - INGREDIENTS AND OCCUPATIONAL EXPOSURE LIMITS

| Chemical Name | CAS Number | % by Weight | OSHA PEL | ACGIH |
|-----------------------|------------|-------------|----------|---------|
| Chloronated Solvents | 127-18-4 | 55 | N/A | 100 ppm |
| Aromatic Hydrocarbons | 1330-20-7 | 45 | 100 ppm | 100 ppm |

SECTION 3 - PHYSICAL DATA

| | | | | |
|------------------------------|---|--|----------------------------|------------------|
| Boiling Point | 250 - 280 degrees F | | Solubility in Water | 0.6 |
| Melting Point | N/A | | Specific Gravity | 1.33 (water = 1) |
| Vapor Pressure | 12 mm Hg at 68 deg F | | Evaporation Rate | undetermined |
| Vapor Density | 5.1 (air = 1) | | Water Reactive | no |
| | | | Percent Volatile | 100% (by volume) |
| Appearance & Odor | Clear liquid with characteristic aromatic odor. | | | |

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

| | | | | |
|--|--|--|----------------------------|-------|
| Flash Point | 180 degrees F (TCC) | | Flammability Limits | 1 LEL |
| Auto Ignition Temp | N/A | | (in Air) | 7 UEL |
| Extinguisher Media | Carbon dioxide, dry chemical, or foam. Do not use water stream. | | | |
| Special Fire Fighting Procedures | Cool the fire-exposed containers with water. Do not enter a confined fire space without proper protective equipment including a NIOSH approved self contained breathing apparatus. | | | |
| Unusual Fire or Explosion Hazards | During a fire this material may decompose to form hydrogen chloride and possibly phosgene gas. | | | |

SECTION 5 - REACTIVITY DATA

| | | | |
|---|-----------------------|----------|----------------------------|
| Stability | Stable | X | Conditions to Avoid |
| | Unstable | | |
| Incompatibility (Materials to Avoid) Avoid strong alkalies | | | |
| Hazardous Decomposition Products Carbon dioxide, carbon monoxide, and unidentified organics. May decompose to form hydrogen chloride and possibly phosgene gas. | | | |
| Hazardous Polymerization | May Occur | | Conditions to Avoid |
| | Will Not Occur | X | |

SECTION 6 - SPILL OR LEAK PROCEDURES

| | |
|---|---|
| Steps to be taken if material is released: | Eliminate potential sources of ignition. Soak up with a non combustible absorbent and place in drums for proper disposal. Flush area with water. |
| Waste disposal methods: | Dispose of in an appropriate disposal facility in compliance with federal, state, and local regulations. |
| Precautions to be taken during handling and storage: | Keep container tightly closed. Store in a cool, dry place. Vapors are heavier than air and will collect in low places. Ground containers when transferring. |

SECTION 7 - HEALTH HAZARD DATA

| | | | | |
|---------------------------------|---------------------|----------|--------------------|----------|
| Primary Routes of Entry: | Inhalation | X | Ingestion | |
| | Skin Contact | X | Eye Contact | X |

SYMPTOMS OF OVEREXPOSURE:

| | |
|----------------------|---|
| Inhalation: | Light headedness, dizziness, drowsiness, narcosis, unconsciousness. |
| Ingestion: | Light headedness, dizziness, drowsiness, narcosis, unconsciousness. |
| Skin Contact: | Can cause defatting of the skin resulting in irritation and dermatitis. |
| Eye Contact: | Irritating to the eyes and mucous membranes |

EMERGENCY FIRST AID PROCEDURES:

| | |
|----------------------|--|
| Inhalation: | Remove victim to fresh air. Provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention. |
| Ingestion: | Do NOT induce vomiting. If vomiting occurs, keep head below hips to avoid aspiration of liquid into lungs. Get medical attention. |
| Skin Contact: | Wash with soap and water. Remove contaminated clothing. If irritation persists, get medical attention. |
| Eye Contact: | Flush eyes with water for at least 15 minutes. Get medical attention. |

SECTION 8 - SPECIAL PROTECTION INFORMATION

| | |
|--|--|
| Respiratory Protection: | Use a NIOSH approved organic vapor respirator if there is a chance of overexposure or if vapors exceed the recommended TLV or PEL |
| Skin Protection: | If excessive exposure is expected, use chemical resistant gloves to minimize skin contact. This material can be absorbed through the skin. |
| Eye Protection: | Wear safety goggles to eliminate the possibility of splashing the material into eyes. |
| Ventilation: | Use explosion proof ventilation equipment to keep the vapor concentrations below the recommended PEL and TLV. |
| Other Protective Clothing or Equipment: | |

The information contained herein is taken from sources or based on data believed to be reliable. However, FMS Corporation makes no warranty regarding the correctness of these data or the results obtained from the use thereof.